

roll covers for the paper making industry

→ Reeling section

Reel drums | Winder drums | Rider rolls | Reel spools

Compound	Machine position	Hardness	Cover thickness	Features
P Series Rubber	Reel drums	50 - 100 P&J	8 - 25 mm	<ul style="list-style-type: none"> • high elasticity • excellent abrasion resistance • high friction coefficient • stable, defined surface roughness
H Series Rubber	Reel drums Winder drums	50 - 100 P&J	8 - 25 mm	<ul style="list-style-type: none"> • excellent resistance to ozone and UV radiation • antistatic properties available • excellent resistance to abrasion, temperature and fatigue
U Series Polyurethane	Reel drums Rider rolls	70 - 90 P&J	8 - 25 mm	<ul style="list-style-type: none"> • excellent abrasion resistance • optional sandwich design – excellent dampening properties, wide nip for perfect reeling results
K Series Rubber	Reel spools	10 - 35 P&J	8 - 15 mm	<ul style="list-style-type: none"> • good resistance to shocks and impacts • good dampening properties • optional electric conductivity
Q.lite Series Polyurethane	Reel spools	10 - 30 P&J	5 - 20 mm	<ul style="list-style-type: none"> • excellent wear resistance and impact strength • good tear strength

These overviews are supposed to give a general idea of what we provide. Different hardness rates are available on application. Surface design/finish, elasticity and functional properties can be designed to any special requirements.