

roll covers for the sheet metal industry

→ Sheet metal forming

Machine position	Compound	Hardness	Features
S-rolls (drawing and brake rolls), driving and calendering rolls, carrier and guide rolls, contact rolls	7P41 Rubber	60 - 85 ShA	<ul style="list-style-type: none"> • good abrasion and cutting resistance • good resistance to oil • cover colour: red
	Q.tera Polyurethane	70 - 95 ShA	<ul style="list-style-type: none"> • excellent wear resistance • optimum cutting resistance • optimum physical and mechanical properties • excellent resistance to oil • cover colour: blue
	Q.flex Polyurethane	70 - 80 ShA	<ul style="list-style-type: none"> • excellent wear resistance • good cutting resistance • very good dynamic properties • resistant to oil • cover colour: yellow
	Q.lite Polyurethane	85 - 95 ShA	<ul style="list-style-type: none"> • excellent wear resistance • good cutting resistance • very good dynamic properties • resistant to oil • cover colour: black
	25F1 Polyurethane	90 ShA	<ul style="list-style-type: none"> • excellent abrasion resistance • optimum cutting resistance • good shock and impact resistance • excellent resistance to oil • special compound with a high friction coefficient over a long period of operation • cover colour: green

These overviews are supposed to give a general idea of what we provide. Different hardness rates are available on application. Colour, surface design/finish, elasticity and functional properties can be designed to any special requirements.